

## HVAC Union Rubber Bellows

### Specification

Commercial quality EPDM bellows intended primarily for HVAC water applications - LT heating, waste, sanitary, chilled.

**Not suitable** for drinking water, contaminated water or mineral oil products.

### Materials

- Liner EPDM
- Reinforcement Nylon chord
- Cover EPDM
- Union Iron, BSP

### Rating

10 Barg @ 20 °C to 6 Barg @ 95 °C.  
Vacuum rating 400 mmHg.

Size	Length	Axial Comp.	Axial Ext.	Lateral	Angular	Stock code
in.	mm	mm	mm	mm	degree	
DN020-3/4"	200	22	6	22	45	R0020FTUEBSP
DN025-1"	200	22	6	22	45	R0025FTUEBSP
DN032-1 1/4"	200	22	6	22	45	R0032FTUEBSP
DN040-1 1/2"	200	22	6	22	45	R0040FTUEBSP
DN050-2"	200	22	6	22	45	R0050FTUEBSP
DN065-2 1/2"	240	22	6	22	45	R0065FTUJBSP
DN080-3"	240	22	6	22	45	R0080FTUJBSP

Movements are non concurrent



### Product by FlexEJ Ltd

For technical assistance & sales  
t: +44 (0)1384 881188  
e: sales@flexej.co.uk